



PVA DRYWALL PRIMER
NO. PX010 (P10)



PRODUCT INFORMATION

KILZ® PVA Interior Primer is designed for use on new drywall. It is a fast-drying, interior latex primer formulated to prime and seal new, uncoated drywall and reduce the number of topcoats required to achieve a uniform, professional quality finish.

RECOMMENDED USES:

Recommended Use on:
• New Drywall/Gypsum Board

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. PX010 (P10) 3.78 L (128 fl oz) / 59 mL (2 fl oz)

Resin Type: PVA

Weight per Gallon: 4.9 kg (10.9 lb)

% Solids by Volume: 26% +/- 2%

% Solids by Weight: 42% +/- 2%

VOC: < 100 g/L

Flash Point: N/A

Viscosity: 105 - 115 KU

Recommended Film Thickness:

Wet: 136 µm / Dry: 35 µm @ 28 m² per 3.78 L
(5.3 mils / 1.4 mils @ 300 sq ft/gal)

Wet: 102 µm / Dry: 26 µm @ 28 m² per 3.78 L
(4.0 mils / 1.0 mils @ 400 sq ft/gal)

Coverage: 28-37 m² per 3.78 L (300-400 sq ft/gal) depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon / Polyester Blend

Roller: 10 mm - 13 mm (3/8" - 1/2" nap)

Airless Spray: Fluid pressure of 17 MPa - 22 MPa (2400 psi - 3200 psi)

Tip: .38 mm - .53 mm (.015" - .021")

Filter: 60 mesh

Dry Time: @ 25°C (77°F), 50% RH

Longer dry time required in cooler temperatures and in higher humidity.

To Touch: 30 Minutes

To Recoat: 2 hours

SURFACE PREPARATION:

Cover all nail and screw heads with joint compound according to directions and sand to smooth surface.

Tape drywall and apply joint compound and allow to fully cure according to directions prior to priming.

Sand to smooth surface before priming.

Wipe off dust with a damp cloth, allow to dry thoroughly

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or visit www.epa.gov/lead.

CLEAN UP:

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

IMPORTANT! Do not open can without reading instructions.

- Interior use only.
- For use on uncoated drywall only.
- Do not use on floors.
- Do not use when air and surface temperatures are below 10°C (50°F) or above 32°C (90°F).
- Allow 2 weeks for full cure before washing or cleaning.
- Do not use over glossy surfaces.
- Shelf life under normal conditions is two years unopened.

COMPLIES WITH THE BELOW AS OF 10/01/2018

Canadian EPA (CEPA) SOR/2009-264	YES
GREENGUARD®	YES
LEED v.4 [†]	YES

[†]Please visit www.usgbc.org/LEED for additional details. GREENGUARD is a registered trademark of UL Company.

GENERAL INFORMATION:

CAUTION IRRITANT MAY IRRITATE EYES AND SKIN. Avoid contact with eyes, skin and clothing. Do not breathe fumes. Keep out of reach of children. Wear eye protection and protective clothing. Use only with adequate ventilation.

FIRST AID TREATMENT: Contains KAOLIN CALCINED, STYRENE/ACRYLIC COPOLYMER and TITANIUM DIOXIDE. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 20 minutes. If on skin, rinse well with water. If inhaled, move person to fresh air.